



PAT

PAT

DS350 CONSOLE UPGRADE INSTRUCTIONS

Part Number 031-300-340-043

NOTICE

The information in this document is subject to change without notice.

PAT makes no warranty of any kind with regard to this material, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose.

PAT shall not be liable for errors contained in this manual or for incidental or consequential damages in connection with the furnishing, performance, or use of this manual. This document contains proprietary information that is protected by copyright.

All rights are reserved.

No part of this document may be photocopied, reproduced, or translated to another language without the prior written consent of PAT.

EPROM replacement in Central Unit

1. Remove cover, from central unit.
2. If current System Software is older than MGVT v2.4, then **Data Software** must also be upgraded to meet requirements.

CAUTION: Before handling the EPROM, discharge any static electricity from your body by touching a grounded point. The EPROM could be damaged by static electricity.

3. Remove the old SYSTEM or DATA EPROM, from the main board. Be careful to pull the EPROM out, without bending the legs. Refer to drawing above.

NOTE: The notch on the EPROM and in the socket determines the correct orientation of the EPROM.

Refer to the drawing below for correct EPROM locations.

4. Carefully align the new EPROM legs with the socket and push the EPROM into place. Be careful not to bend any of the legs.
5. Install the cover and tighten screws, making sure the rubber gasket, is positioned correctly, to prevent any moisture, from entering the central unit.



